

ODE-3-140041-3F12

Optidrive E3 VFD Datasheet

1,5 kW (2 HP), 4,1 A, 380-480 V, 3PH
Variadores de frecuencia con filtro CEM



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	5,6 A
Supply Fuse or MCB (Type B)	10 A

Output Ratings

Motor Output Rating	1,5 kW (2 HP)
Output Voltage	0 – Supply Voltage
Output Current	4,1 A

Cable Information

Max Supply Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	CEM interno
Brake Transistor	Sin transistor de freno interno
Enclosure	IP20
Display	
PCB Coating	


Dimensions

Size	1
Height	173 mm (6,81 in)
Width	83 mm (3,27 in)
Depth	123 mm (4,84 in)
Weight	1 kg (2,2 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	165 mm (6,5 in)
Width	125 mm (4,92 in)
Depth	235 mm (9,25 in)
Weight	1,2 kg (2,65 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

 **Invertertek**
Drives.com